

vMSIS3-CSD-C825-T



vMSIS3-CSD-C825-T- Vlatacom Multi Sensor Imaging System 3 - Cooled Standard Definition

Product Description

The vMSIS3-CSD-C825-T is a state-of-the-art monitoring and surveillance system that integrates various high definition imaging sensors and provides ultra-long range target detection, recognition, and identification based on highly advanced sensors, optics, and image processing. The system consists of a cooled MWIR standard definition thermal imager, a color low light day/night high definition imager, and an optional SWIR imager. Each of them employs long range optics and a real-time image stabilization system. The vMSIS3-CSD-C825-T utilizes a pan/tilt platform with gyro-stabilization. The entire system operates in a large temperature range and various climatic conditions. The entire system can be controlled, monitored, and have its parameters adjusted from a remote/local control center or an optional control console.

The cooled MWIR thermal imager exposes targets even in total darkness and during atmospheric impairments caused by: rain, snowfall, fog, haze, dust, sandstorm and/or smoke. This makes the system suitable for both land and coastal applications.

The color low light imager provides additional details during day and low-light conditions. The optional SWIR imaging further improves target visualization and tracking in rough weather and atmospheric conditions (e.g. fog and smoke). Optional video stabilization, image enhancement, video-tracking, motion detection algorithms, and mapping toolkit are also available. Additionally, the system can include optional components like an: eye-safe laser rangefinder, a digital magnetic compass, and a GPS.

Key Features

- Modular multi-sensor high definition imaging system
- Superior cooled MWIR standard definition thermal imager
- Long range color low-light high definition imager
- Crisp high resolution image
- Excellent range performance
- High-performance T-shaped gyro stabilized pan-tilt unit
- Optional SWIR imaging
- Remotely or locally controlled
- Optional control and monitoring console with one or three monitors
- Rugged enclosure
- 24/7/365 operation
- Optional features: video stabilization, image enhancement, video tracking, motion detection algorithms and mapping toolkit



Control and Monitoring

- Remotely/locally controlled and monitored
- Video streams from each imager can be easily monitored

Specifications:

MWIR thermal imager		Color low light imager	
Array format:	640 x 512 pixels	Array format:	1974 x 1110 pixels
Detector type:	InSb FPA	Detector type:	Single CMOS / RGB Bayer
Resolution:	0.3 Megapixels	Resolution:	2.2 Megapixels
Pixel pitch:	15µm	Pixel size:	5 µm
Spectral band:	3.0µm to 5.0µm	Sensor sensitivity:	<0.0025lx
NETD:	25mK@50% well fill capacity (mean)	Minimal subject illumination:	0.04lx (F4, 30 fps, 50IRE, +72db, color) (Night level 2 - half moon or cloudy full moon equivalent)
Cooler MTTF:	10,000 hours	Optics:	Motorized continuous zoom lens
Optics:	Motorized continuous zoom lens	Focal length:	12mm - 550mm
Focal length:	38mm - 825mm		
F#:	4		
SWIR imager - optional		Laser rangefinder - optional	
Array format:	640 x 512 pixels	Range:	10 km for target 2.3m x 2.3m, 30% reflectivity and 23.5km visibility
Detector type:	InGaAs 2D array	Wavelength:	1.54µm
Resolution:	640 x 512	Range of measurement:	80m to 20,000m
Pixel pitch:	20µm	Fully Eye-safe:	Class 1
Spectral band:	0.9µm to 1.7µm		
Noise (RMS):	<400 electrons Low Gain <60 electrons High Gain		
Optics:	Motorized continuous zoom lens		
Focal length:	100mm - 1000mm		
Pan tilt platform		General	
Azimuth movement range:	N x 360°	Interface:	Ethernet 100/1000BaseT
Elevation movement range:	From -40° to + 40°	Power supply/Consumption:	24VDC or 230VAC, 450W
Azimuth speed range:	From 0.005°/sec to 60°/sec	Dimensions (WxDxH):	830mm x 658mm x 533mm
Elevation speed range:	From 0.005°/sec to 60°/sec	Weight:	Up to 76 kg (with SWIR and LRF; w/o connection box)
		Operational temperature:	-25°C to 55°C
Operating console (optional)			
Displays:	1 - 3 depending on choice		
Resolution:	Up to full HD (1920 x 1080)		

Detection, Recognition, and Identification Ranges		
Human		
	Geometric calculation*	
	Real world**	
Vehicle		
	Geometric calculation*	
	Real world**	

(*) Geometrical calculation for system IFOV (pixel size / maximum focal length).

(**) Calculated with NVThermIP model, according to STANAG 4347: 50% probability at 0.2/km atmospheric attenuation factor and 2K temperature difference. Actual range may vary depending on environmental conditions, camera set-up, type of display and user experience.



Address:
Vlatacom institute d.o.o.
Milutina Milankovića 5
11070 Belgrade, Serbia

tel: +381 11 377 11 00
fax: +381 11 377 11 99
marketing@vlatacom.com
www.vlatacom.com